

ANTIFREEZE



Radiator



All-Season Cooling

SUPER GREEN ANTIFREEZE -37°C

DESCRIPTION AND APPLICATION

Lubran Super Antifreeze is a high-performance, all-season coolant fluid produced by adding high-performance corrosion inhibitors to ethylene glycol. It is a versatile coolant fluid that can be used in all types of radiators.

FEATURES AND BENEFITS

- Provides excellent protection against freezing in winter and boiling in summer.
- Compatible with radiator materials such as aluminum, cast iron, and metal alloys, as well as elastomers and sealing components used in the cooling system of internal combustion engines.
- Prevents rust and corrosion formation and ensures maximum protection.
- Use ready-to-use for maximum performance. Do not add water.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. In case of contact with skin or eyes, wash with plenty of soapy water and seek medical attention if necessary. If ingested, do not induce vomiting and seek emergency medical help. If vapors are inhaled, take deep breaths and seek medical assistance if needed. Used Lubran motor oils should not be disposed of in the trash, sewer, or environment; they should be collected in waste oil containers in accordance with local regulations and delivered to authorized recycling centers. It should not be mixed with any petroleum products or chemicals. It should not be burned in stoves or boilers. Store in places out of reach of children. Empty containers should not be disposed of in the trash or left in the environment; they should be delivered to licensed recycling organizations. For detailed information, please refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran motor oil packaging should not be exposed to prolonged direct sunlight. The packaging should not come into contact with water. The oils should not come into contact with dust and should be kept away from dusty environments. The ambient temperature should not exceed 40°C. The proper use of this product and compliance with applicable laws and regulations are entirely the responsibility of the user. Lubran cannot be held responsible for any damage or loss arising from the abnormal or improper use of the product or any hazards and consequences related to the product's composition.

PHYSICAL PROPERTIES	ORGANIC ANTIFREEZE
Color and Appearance	Blue and Clean
Density, kg/m ³ , at 15°C	1,06
PH, 20°C'de,	8,3
Freezing Point, °C	-37
Boiling Point, °C	120

PACKAGING TYPES

