


## WELLIX DPF 0W-30



### HIGH-PERFORMANCE DPF OILS

#### DESCRIPTION AND APPLICATION

Lubran 0W-30 is a synthetic engine oil designed to meet the high-performance requirements of new generation engines. It is suitable for use in gasoline and diesel-powered passenger and light commercial vehicles. Its special formula provides effective engine cleaning, superior wear protection, and noticeable fuel economy.

#### FEATURES AND BENEFITS

- Thanks to its new additive technology, it provides excellent protection against wear even under the most challenging operating conditions.
- Improved friction reduction ensures fuel economy.
- High oxidation stability retains its properties until the next oil change.
- Effective cleaning minimizes deposits and accumulation.
- Shows extra performance compared to traditional engine oils.
- Its unique formula stands out with its fuel economy and performance.

#### PERFORMANS

API: SN/CF ACEA: A1/B1, C2/C3 GM: Recommended for use in Dexos 2 vehicles.

#### HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. If it comes into contact with skin or eyes, the affected area should be washed thoroughly with soap and water, and medical assistance should be sought if necessary. In case of ingestion, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, ensure exposure to fresh air and seek medical help if required. Used Lubran motor oil should be collected in appropriate waste oil collection containers and delivered to authorized recycling centers in compliance with the applicable waste management regulations. It should not be disposed of in trash, sewage, or nature, and should not be mixed with any other petroleum product or chemical. Containers should not be thrown away or left in the environment but delivered to licensed recycling facilities. The product must not be burned in stoves or boilers. Keep out of the reach of children. For detailed information, please refer to the "Material Safety Data Sheet."

#### STORAGE CONDITIONS

Lubran motor oil packages should not be exposed to prolonged and direct sunlight. Packages should be kept away from dusty environments and must not be in contact with oils. The ambient temperature should not exceed 40°C. It is the sole responsibility of the user to ensure compliance with the intended use of the product and the relevant regulations in force. Lubran cannot be held liable for any damage, harm, or risks arising from improper use or use outside the intended purpose of the product.

#### TYPICAL PROPERTIES

TYPICAL PROPERTIES	METHOD	0W-30
DENSITY, G/CM <sup>3</sup> AT 15°C	ASTM D 4052	0,850
KIN. VISCOSITY, CST AT 100°C	ASTM D 445	9,3-12,6
VISCOSITY INDEX	ASTM D 2270	150
POUR POINT, °C	ASTM D 97	-40
FLASH POINT, °C	ASTM D 92	210

#### PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.  
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE