


## PROLUBE FUL 10W-40 CJ-4



### HEAVY-DUTY DIESEL ENGINE OIL

#### DESCRIPTION AND APPLICATION

Lubran 10W-40 CJ-4 is a fully synthetic engine oil specially formulated for heavy-duty diesel engines. It provides excellent performance in engines using ultra-low sulfur fuels, particulate filter systems, and exhaust gas recirculation (EGR) and selective catalytic reduction (SCR) systems. This oil is compatible with engines meeting Euro IV and higher emission standards.

#### FEATURES AND BENEFITS

- Lubran 10W-40 CJ-4, with its unique System Pro Technology™, increases oil life by up to 45%, providing enhanced and maximum oil change intervals, effectively protecting the engine in the long term.
- Its low ash formula minimizes deposits and pressure build-up, ensuring better engine performance by preventing clogging of oil molecules.
- Lubran's System Pro Technology™ maintains viscosity stability, preventing harmful residue accumulation and oxidation, ensuring the engine's longevity.
- This high-tech oil has enhanced thermal resistance, ensuring viscosity stability even under extreme conditions. Thus, Lubran 10W-40 CJ-4 extends engine life and increases the durability of modern engines.

#### PERFORMANCE

Meets the requirements of ACEA E6, E7, E9, E8, E11; API CJ-4; JASO DH-2; CAT ECF-3; Cummins CES 20081; Deutz DQC IV-18 LA; DTRF15C110 (MB 228.51); Mack EO-0 Premium Plus, EOS-4.5; MTU Oil Category 3.1; RVI RLD-3; Volvo CNG VDS-4, VDS-4.5; MAN M 3271-1 and M 3477. Suitable for Iveco trucks requiring ACEA E6, E7, and E9.

#### HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran engine oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. In case of contact with skin or eyes, wash with plenty of soapy water and seek medical attention if necessary. Do not induce vomiting if swallowed and seek immediate medical attention. When vapors are inhaled, move to fresh air and seek medical advice if needed. Used Lubran engine oils should not be disposed of in garbage, sewage, or receiving environments. They should be collected in waste oil containers in accordance with applicable regulations and delivered to authorized recycling centers.

#### STORAGE CONDITIONS

Lubran motor oil packages should not be exposed to prolonged and direct sunlight. Packages should be kept away from dusty environments and must not be in contact with oils. The ambient temperature should not exceed 40°C. It is the sole responsibility of the user to ensure compliance with the intended use of the product and the relevant regulations in force. Lubran cannot be held liable for any damage, harm, or risks arising from improper use or use outside the intended purpose of the product.

#### TYPICAL PROPERTIES

TYPICAL PROPERTIES	METHOD	10W-40
DENSITY, G/CM <sup>3</sup> AT 15°C	ASTM D 4052	0,860
KIN. VISCOSITY, CST AT 100°C	ASTM D 445	14,2
VISCOSITY INDEX	ASTM D 2270	138
POUR POINT, °C	ASTM D 97	-39
FLASH POINT, °C	ASTM D 2270	220

#### PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.  
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE