


ATF DEXRON II



AUTOMATIC TRANSMISSION AND DIFFERENTIAL OIL

DESCRIPTION AND APPLICATION

ATF Dexron II is an automatic transmission oil produced with high-quality base oils and anti-corrosion additive packages designed for use in automatic transmissions and differentials of vehicles. It offers high oxidation resistance, prevents foaming, and ensures superior corrosion protection.

FEATURES AND BENEFITS

- High viscosity index allows for smooth and effective use in all four seasons.
- Enhanced anti-wear properties extend service life.
- Special additive technology prevents foam formation and reduces wear.
- Anti-corrosion additives provide excellent corrosion protection.

PERFORMANCE

GM DEXRON IID, MB- 236.1, IIE, ZF TE ML 14A/14B/17C, GM ALLISON C-4, FORD MERCON, TES-229, TES-389, TASA, VOLVO 97341.
Meets the performance requirements of these specifications.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. If it comes into contact with skin or eyes, the affected area should be washed thoroughly with soap and water, and medical assistance should be sought if necessary. In case of ingestion, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, ensure exposure to fresh air and seek medical help if required. Used Lubran motor oil should be collected in appropriate waste oil collection containers and delivered to authorized recycling centers in compliance with the applicable waste management regulations. It should not be disposed of in trash, sewage, or nature, and should not be mixed with any other petroleum product or chemical. Containers should not be thrown away or left in the environment but delivered to licensed recycling facilities. The product must not be burned in stoves or boilers. Keep out of the reach of children. For detailed information, please refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran motor oil packages should not be exposed to prolonged and direct sunlight. Packages should be kept away from dusty environments and must not be in contact with oils. The ambient temperature should not exceed 40°C. It is the sole responsibility of the user to ensure compliance with the intended use of the product and the relevant regulations in force. Lubran cannot be held liable for any damage, harm, or risks arising from improper use or use outside the intended purpose of the product.

TYPICAL PROPERTIES

TYPICAL PROPERTIES	METHOD	DEXRON II
DENSITY, G/CM ³ AT 15°C	ASTM D 4052	0,865
KIN. VISCOSITY, CST AT 100°C	ASTM D 445	6-7,5
VISCOSITY INDEX	ASTM D 2270	140
POUR POINT, °C	ASTM D 97	-35
FLASH POINT, °C	ASTM D 92	210

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE