


## ATF DEXRON III



### HYDRAULIC POWER STEERING FLUID

#### DESCRIPTION AND APPLICATION

ATF DEXRON III is a high-performance synthetic automatic transmission oil produced by blending refined synthetic base oils with additive packages using advanced technology. It is specifically designed for automatic transmissions that meet GM Dexron and Ford Mercon specifications. Suitable for power-shift transmissions, power steering systems, and hydraulic units.

#### FEATURES AND BENEFITS

- Synthetic properties and a wide operating temperature range ensure smooth operation in automatic transmissions.
- High stability and oxidation resistance provide long-lasting use.
- Special additive technology prevents corrosion and foam formation.
- High viscosity index maintains superior performance and minimizes wear, ensuring an extended service life.

#### PERFORMANCE

GM DEXRON III, DEXRON IIIH, ALLISON C4, MB 236.1/236.5/236.9, TASA, MERCON, ZF TE-ML-02F0 03D, 04D, 09B, 11B, 14A, 16L, 17C, Voith 55.6336.X(X(G1363), MAN 339 Type Z-2/V-2, MAN 339 Type Z-1/V-1 specifications.

#### HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. If it comes into contact with skin or eyes, the affected area should be washed thoroughly with soap and water, and medical assistance should be sought if necessary. In case of ingestion, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, ensure exposure to fresh air and seek medical help if required. Used Lubran motor oil should be collected in appropriate waste oil collection containers and delivered to authorized recycling centers in compliance with the applicable waste management regulations. It should not be disposed of in trash, sewage, or nature, and should not be mixed with any other petroleum product or chemical. Containers should not be thrown away or left in the environment but delivered to licensed recycling facilities. The product must not be burned in stoves or boilers. Keep out of the reach of children. For detailed information, please refer to the "Material Safety Data Sheet.

#### DEPOLAMA KOŞULLARI

Lubran motor oil packages should not be exposed to prolonged and direct sunlight. Packages should be kept away from dusty environments and must not be in contact with oils. The ambient temperature should not exceed 40°C. It is the sole responsibility of the user to ensure compliance with the intended use of the product and the relevant regulations in force. Lubran cannot be held liable for any damage, harm, or risks arising from improper use or use outside the intended purpose of the product.

#### TYPICAL PROPERTIES

TYPICAL PROPERTIES	METHOD	DEXRON III
DENSITY, G/CM <sup>3</sup> AT 15°C	ASTM D 4052	0,865
KIN. VISCOSITY, CST AT 100°C	ASTM D 445	7-7,5
VISCOSITY INDEX	ASTM D 2270	160
POUR POINT, °C	ASTM D 97	-39
FLASH POINT, °C	ASTM D 92	210

#### PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.  
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE