


ATF DEXRON VI



Synthetic Automatic Transmission Fluid

DESCRIPTION AND APPLICATIONS

ATF DEXRON VI is a high-performance synthetic automatic transmission fluid formulated by blending synthetic base oils with state-of-the-art additive combinations. It is specifically developed for modern automatic transmissions requiring GM Dexron or Ford Mercon specifications and can also be used in power-shift transmissions, steering systems, and hydraulic units.

FEATURES AND BENEFITS

- Provides excellent thermal oxidation stability.
- Extends the lifespan of both the oil and the transmission with its anti-wear properties and resistance to chemical degradation.
- Provides superior anti-vibration ability and torque transfer capacity.
- Ensures smooth gear shifting even under the most demanding conditions with friction-reducing properties and outstanding performance at low temperatures, enhancing driving comfort.
- Compatible with vehicles requiring General Motors Dexron III or Dexron II performance levels.

PERFORMANCE

Meets General Motors Dexron VI, JASO 1A LV, MB 236.15, MB236.16, Honda ATFTType 3.1 performance specifications.

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Lubran engine oil should not come into contact with skin and eyes, should not be swallowed, and its vapors should not be inhaled. In case of contact with skin and eyes, wash with plenty of soap and water and seek medical attention if necessary. If swallowed, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, breathe deeply and seek medical attention if necessary. Used Lubran engine oils should not be discharged into the trash, sewer, or the receiving environment. They should be collected in waste oil collection containers that comply with applicable legislation and delivered to authorized recycling centers. They should not be mixed with any petroleum products or chemicals. They should not be burned in stoves or boilers. They should be kept out of reach of children. Empty containers should not be thrown in the trash or left in the receiving environment; they should be delivered to licensed

STORAGE CONDITIONS

Lubran engine oil containers should not be exposed to direct sunlight for extended periods. Containers should not come into contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. The ambient temperature should not exceed 40°C. The user is solely responsible for using this product as intended and complying with applicable laws and regulations. Lubran cannot be held responsible for any damage or loss that may arise from abnormal or improper use of the product, or for any inherent hazards or consequences.

TYPICAL FEATURES

PHYSICAL PROPERTIES	METHOD	DEXRON VI
Density, g/cm ³ at 15°C	ASTM D 4052	0,850
Kin. Viscosity, cSt, 100°C	ASTM D 445	5,6-9,3
Viscosity Index min.	ASTM D 2270	150
Pour Point, °C, max.	ASTM D 97	-39
Flash Point, °C, min	ASTM D 92	210

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE