

GEARLUBE EP 75W-140



Gear Oils



Heavy Vehicles



Semi-Synthetic

Fully Synthetic Heavy-Duty Gear Oil

DESCRIPTION AND APPLICATION

GearLube EP 75W-140 is a fully synthetic heavy-duty gear oil with high performance and long-term stability. It is formulated to provide exceptional performance in wide temperature ranges, protecting against thermal degradation, oxidation, wear, and corrosion. This oil is designed to deliver excellent stability and high viscosity index with superior film strength under high loads, even in extreme conditions. Thanks to this technology, it provides effective lubrication in harsh environments under heavy loads.

FEATURES AND BENEFITS

- Protects the gear system from wear with high-temperature stability and EP additives.
- High shear stability prevents film breakdown and ensures consistent viscosity.
- Provides excellent corrosion protection, making gear operations smoother.
- Resists oxidation at high temperatures, maintaining long-lasting performance.
- Increases efficiency, extending oil drain intervals and reducing overall operating costs.

PERFORMANCE

Meets API GL-5 performance specifications.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran gear oil should be kept away from skin and eyes and should not be ingested or inhaled. In case of contact with skin or eyes, wash immediately with soapy water. If swallowed, seek medical attention. In case of vapor inhalation, move to fresh air and consult a doctor if necessary. Used oil must be disposed of in compliance with local regulations. Avoid releasing used oil into the environment. Empty containers must not be reused or burned. Keep out of reach of children and store in properly ventilated places. For more detailed information, refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran gear oil containers should not be exposed to direct sunlight for extended periods. Containers should be stored in environments with temperatures not exceeding 40°C. Protect from physical damage and contamination. Use the product in accordance with its intended purpose to maintain its quality and ensure safe use.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	EP 75W-140
Density, g/cm ³ at 15°C	ASTM D 4052	0,862
Kinematic Viscosity, cSt, at 100°C	ASTM D 445	25,5
Viscosity Index	ASTM D 2270	150
Pour Point, °C	ASTM D 97	-42
Flash Point, °C	ASTM D 92	205

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE