


GEARLUBE EP 85W-140



Gear Oil



Heavy Duty



Full Synthetic

High-Performance Heavy-Duty Automotive Gear Oil

DESCRIPTION AND APPLICATION

GearLube EP 85W-140 is a high-performance heavy-duty gear oil produced by combining high-quality paraffinic base oils and extreme pressure (EP) additives. It is suitable for manual transmissions and differentials in automobiles, trucks, buses, light commercial vehicles, agricultural vehicles, construction vehicles, and many other mechanical systems operating under four-season conditions.

FEATURES AND BENEFITS

- Contains extreme pressure (EP) additives to prevent wear, providing excellent protection for gear components.
- Exhibits very high viscosity properties, ensuring smooth and consistent performance even at high temperatures.
- Protects against rust, corrosion, and foam formation, providing superior performance under harsh conditions.
- High thermal stability and oxidation resistance keep gear systems clean and efficient.
- Reduces leakage by maintaining tight sealing, extending the life of gaskets and sealing materials.

PERFORMANCE

Meets the following performance specifications: API GL-5; MIL-L-2105D; MB 235.0; MAN 342 Type M-1/2; ZF TE ML 05A, 7A, 12E, 16B, C, D, 17B, 19B, 21A.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran gear oil should be kept away from skin and eyes and should not be ingested or inhaled. In case of contact with skin or eyes, wash immediately with soapy water. If swallowed, seek medical attention. In case of vapor inhalation, move to fresh air and consult a doctor if necessary. Used oil must be disposed of in compliance with local regulations. Avoid releasing used oil into the environment. Empty containers must not be reused or burned. Keep out of reach of children and store in properly ventilated places. For more detailed information, refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran gear oil containers should not be exposed to direct sunlight for extended periods. Containers should be stored in environments with temperatures not exceeding 40°C. Protect from physical damage and contamination. Use the product in accordance with its intended purpose to maintain its quality and ensure safe use.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	GEARLUBE EP 85W-140
Density, g/cm ³ at 15°C	ASTM D 4052	0,890
Kinematic Viscosity, cSt, at 100°C	ASTM D 445	26,5-30
Viscosity Index	ASTM D 2270	97
Pour Point, °C	ASTM D 97	-18
Flash Point, °C	ASTM D 92	225

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE