



ATF LT 71141

Automatic Transmission Fluid

DESCRIPTION AND APPLICATION

ATF LT 71141 is designed to meet the stringent requirements of high-performance automatic service transmissions. It provides exceptional gear-shifting and power transmission performance. While maintaining excellent performance in cold weather, it prevents degradation caused by heat at high operating temperatures.

FEATURES AND BENEFITS

- Features a high viscosity index and can be used year-round.
- Prolongs the life of the system with its high wear prevention properties.
- Advanced additive package protects the system against rust and foam formation.
- Corrosion inhibitor additives ensure optimal protection of the system.

PERFORMANCE

Meets the performance specifications of:

FORD WSS-M2C202-B, BMW: ETL-7045E, MB: 236.11, Jaguar, Land Rover: F N 402, Peugeot, Porsche, Citroën: ATF LT 71141, VW: TL 52162, Voith 55.6336.3x Extended, Drain (G1363), ZF TE-ML 04D/11B/14B/16L, ZF TE-ML 17C.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran automatic transmission fluid should not come into contact with skin or eyes, should not be swallowed, and its vapors should not be inhaled. In case of contact with skin or eyes, rinse thoroughly with soap and water and seek medical attention if necessary. If swallowed, do not induce vomiting and seek emergency medical attention. If vapors are inhaled, take deep breaths and seek medical help if needed. Used Lubran fluids must not be discharged into drains, sewers, or the environment. They should be collected in designated waste oil containers and delivered to authorized recycling centers in accordance with applicable regulations. They must not be mixed with other petroleum derivatives or chemicals and should not be burned in stoves or furnaces. Empty containers should not be disposed of in landfills or the environment but handed over to licensed recycling organizations. For detailed information, you can review the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran fluid packages should not be exposed to direct sunlight for extended periods. Packages must not come into contact with water. Fluids should not come into contact with dust and should be kept away from dusty environments. The ambient temperature should not exceed 40°C. The proper use of this product in compliance with current laws and regulations is the sole responsibility of the user. Lubran cannot be held liable for any damages or adverse effects resulting from improper use, deviations from the intended purpose, or the product's inherent hazards.

TYPICAL PROPERTIES

PHYSICAL PROPERTY	METHOD	LT 71141
Density, g/cm ³ at 15°C	ASTM D 4052	0,845
Kinematic Viscosity, cSt, 100°C	ASTM D 445	7,6
Viscosity Index	ASTM D 2270	170
Pour Point, °C, max	ASTM D 97	-42
Flash Point, °C, min	ASTM D 92	230

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE