

GREEN ATF HYDRAULIC OIL



Hydraulic Steering Gear Fluid

DESCRIPTION AND APPLICATION

This is a mineral-based oil formulated with additives and is a fuel-efficient, green-colored hydraulic steering oil suitable for hydropneumatic suspension, shock absorbers, and hydraulic steering systems.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with the skin or eyes, should not be ingested, and its vapor should not be inhaled. If contact occurs, wash thoroughly with soap and water; seek immediate medical attention if necessary. Vapors should be avoided; if inhaled, move to fresh air and seek help. Used Lubran motor oil must be disposed of legally and through authorized waste oil collection centers. Do not mix with other substances. Empty containers must not be discarded in the environment. Refer to the "Material Safety Data Sheet" for more details.

STORAGE CONDITIONS

Lubran motor oil packages should be stored away from prolonged exposure to direct sunlight. The packaging should remain sealed and be stored in a dust-free environment at temperatures below 40°C. Users are responsible for following all applicable laws and regulations for usage.

| PHYSICAL PROPERTY | METHOD | YEŞİL ATF |
|------------------------------------|-------------|-----------|
| Density, g/cm ³ at 15°C | ASTM D 4052 | 0,869 |
| Kinematic Viscosity, cSt at 100°C | ASTM D 445 | 5-7 |
| Viscosity Index | ASTM D 2270 | 95 |
| Pour Point, °C | ASTM D 97 | -21 |
| Flash Point, °C | ASTM D 92 | 210 |

PACKAGING TYPES

