

POWERFLUID 426



High-Performance Multi-Purpose Tractor Oil

DESCRIPTION AND APPLICATION

LUBRAN Powerfluid 426 is a high-performance, multi-purpose tractor oil designed to meet the requirements of transmissions, hydraulic systems, and wet brakes. It maximizes the performance of agricultural and commercial tractors working under various conditions. This product is formulated with advanced base oils and additive packages to deliver the necessary lubrication performance in demanding applications, particularly in agricultural and construction machinery transmission systems. It is especially suitable for reducing wet brake noise and Power Take-Off (PTO) vibrations.

FEATURES AND BENEFITS

- Provides excellent friction characteristics, ensuring high-level grip and PTO performance, while remaining compatible with clutches and elastomers.
- Offers extended clutch life and reduced oil consumption with its high viscosity index and excellent shear stability.
- Protects yellow metal surfaces from corrosion and wear, offering superior protection.
- Prevents early wear in wet or humid environments, and maintains effective lubrication performance even in extremely low temperatures, thanks to its superior cold weather properties.
- Reduces wear caused by excessive pressure, extends the lifespan of equipment, and lowers maintenance costs.
- Minimizes sludge and oxidation, reducing deposits and extending the life of seals, equipment, and oil.

PERFORMANCE

Compatible with and meets the performance requirements of: AGCO Powerfluid 821 XL, Allison C-4, API GL-4 Caterpillar TO-2, CNH MAT 3505, CNH MAT 3525, Denison UTTO/THF, FORD NH FNHA-2-C-201.00, FORD ESN-M2C134-D, JICASE MS 1204, JOHN DEERE JDM J20D, MASSEY FERGUSON CMS M1145, MASSEY FERGUSON CMS M1143, MASSEY FERGUSON CMS M1141, MASSEY FERGUSON CMS M1135, New Holland WB NWH 410B.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran oil should not come into contact with skin or eyes, should not be swallowed, and its fumes should not be inhaled. If swallowed, medical help should be sought immediately. If fumes are inhaled, fresh air and medical assistance should be sought if necessary. Used Lubran oils should not be disposed of in drains, sewers, or other inappropriate environments but should be collected in designated containers and delivered to authorized recycling centers. Waste oil should not be mixed with other petrochemical products or chemicals. It should not be burned in stoves or boilers. Keep out of reach of children. For further details, refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran oils should be stored in their original packaging in a cool, dry place away from direct sunlight. Avoid contact with dust. The storage temperature should not exceed 40°C. This product should only be used for its intended purpose, and any use contrary to its specifications may result in liabilities and risks for the user.

TYPICAL PROPERTIES

PHYSICAL PROPERTY	METHOD	POWERFLUID 426
Density, g/cm ³ at 15°C	ASTM D 4052	0,890
Kinematic Viscosity, cSt, 100°C	ASTM D 445	9,3-12,3
Viscosity Index	ASTM D 2270	148
Pour Point, °C, max	ASTM D 97	-36
Flash Point, °C, min	ASTM D 92	225

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE