


## PROLUBE 20W-50



Motor Oil



Heavy-Duty



Fully Synthetic

### High-Performance Motor Oils

#### DESCRIPTION AND APPLICATION

Mineral-based oils combined with premium-quality additives are designed to provide high-performance multi-grade motor oils suitable for all seasons. They can be used safely in diesel engines operating under heavy-duty conditions and in all climate conditions, such as in industrial machinery, buses, trucks, minibusses, and passenger cars.

#### FEATURES AND BENEFITS

- High resistance to oxidation. Prevents rust and corrosion formation, ensuring excellent protection against engine wear.
- The high TBN (Total Base Number) value prevents acid formation and ensures superior protection. Extends the oil change interval, saving costs.
- Detergent-dispersant additives prevent deposit formation, keeping the engine clean.
- High viscosity index provides excellent multi-season performance.
- Contains anti-foam additives for better lubrication.
- Helps reduce air pollution by lowering exhaust emissions.
- Provides superior protection and oil consumption control under all climate and operational conditions.

#### PERFORMANCE

API: CF-4/CF/SL/SG, MIL-L-2104 D, ACEA: E3/E2, MB: 228.3, MAN: 3275, VW: 505.00, CAT: TO-2, ALLISON: C3 meet the performance specifications.

#### HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and vapors should not be inhaled. If contact occurs, the affected area should be washed thoroughly with soapy water, and medical attention should be sought if necessary. In case of accidental ingestion, medical assistance should be obtained immediately. Used Lubran motor oils should not be disposed of into sewage systems or open areas but collected in approved containers and delivered to authorized recycling centers. For further details, refer to the "Material Safety Data Sheet."

#### STORAGE CONDITIONS

Lubran motor oil containers should be stored for long periods away from direct sunlight and in dust-free environments. Storage temperatures should not exceed 40°C. The product is the user's responsibility to ensure its intended use complies with legal regulations. Lubran cannot be held liable for damages or risks arising from improper or unauthorized use of the product.

#### TYPICAL PROPERTIES

PHYSICAL PROPERTY	METHOD	PROLUBE 20W-50 CF-4
Density, g/cm <sup>3</sup> at 15°C	ASTM D 4052	0,880
Kinematic Viscosity, cSt, 100°C	ASTM D 445	16,3-21,9
Viscosity Index	ASTM D 2270	120
Pour Point, °C, max	ASTM D 97	-21
Flash Point, °C, min	ASTM D 2270	225

#### PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.  
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE