


WELLIX 5W-30



FULLY SYNTHETIC MOTOR OIL – GASOLINE

DESCRIPTION AND APPLICATION

LUBRAN FULLY SYNTHETIC WELLIX 5W-30 is a fully synthetic motor oil formulated with advanced additives to deliver fuel efficiency for modern passenger car engines. It can be safely used year-round in gasoline engines that require oils meeting API SN (RC) and ILSAC GF-5 performance levels.

FEATURES AND BENEFITS

- Advanced additive technology keeps the engine clean, reduces friction, and ensures long service life with optimal energy savings.
- Its synthetic formulation offers superior protection and fuel efficiency.
- By extending engine life and lubrication intervals, it contributes to fuel savings.
- Delivers full-capacity performance under all climate and road conditions.
- Excellent low-temperature properties eliminate potential wear during cold starts.

PERFORMANCE

Meets the performance specifications of API SN (RC), ILSAC GF-5, GM dexos1 Gen 2, FORD WSS-M2C948-A, FORD WSS-M2C948-B, Fiat 9.55535-CR1, and is suitable for use in Honda, Hyundai, Mazda, Kia, Nissan, and Toyota vehicles.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. If it comes into contact with skin or eyes, the affected area should be washed thoroughly with soap and water, and medical assistance should be sought if necessary. In case of ingestion, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, ensure exposure to fresh air and seek medical help if required. Used Lubran motor oil should be collected in appropriate waste oil collection containers and delivered to authorized recycling centers in compliance with the applicable waste management regulations. It should not be disposed of in trash, sewage, or nature, and should not be mixed with any other petroleum product or chemical. Containers should not be thrown away or left in the environment but delivered to licensed recycling facilities. The product must not be burned in stoves or boilers. Keep out of the reach of children. For detailed information, please refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran motor oil packages should not be exposed to prolonged and direct sunlight. Packages should be kept away from dusty environments and must not be in contact with oils. The ambient temperature should not exceed 40°C. It is the sole responsibility of the user to ensure compliance with the intended use of the product and the relevant regulations in force. Lubran cannot be held liable for any damage, harm, or risks arising from improper use or use outside the intended purpose of the product.

TYPICAL CHARACTERISTICS

PHYSICAL PROPERTY	METHOD	FULL SYN 5W-30
Density, g/cm ³ at 15°C	ASTM D 4052	0,850
Kinematic Viscosity, cSt at 100°C	ASTM D 445	9,3-12,5
Viscosity Index, min.	ASTM D 2270	150
Pour Point, °C, max.	ASTM D 97	-38
Flash Point, °C, min.	ASTM D 92	210

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE