


PROLUBE FULL 5W-40



HIGH-PERFORMANCE SYNTHETIC HEAVY-DUTY DIESEL ENGINE OILS

DESCRIPTION AND APPLICATION

It is a synthetic heavy-duty diesel engine oil. Wellix DPF 5W-40 CK-4 is compatible with diesel engines equipped with EGR, as well as exhaust systems such as DPF, DOC, and SCR. It is used in high-speed, four-stroke heavy-duty diesel vehicles and is suitable for heavy-duty trucks and machinery operating in transportation, construction, and agriculture sectors.

FEATURES AND BENEFITS

- Provides excellent protection against oxidation, deposits, and potential engine wear even under the most severe operating conditions.
- Enhanced friction-reducing properties contribute to improved fuel economy.
- High oxidation stability helps neutralize harmful acids.
- Low volatility reduces oil consumption.
- Delivers superior performance compared to conventional engine oils.
- Low ash content prevents friction and wear, maintaining piston cleanliness.
- Supports environmental protection through effective exhaust emission control.

PERFORMANCE

Meets the performance specifications of API CK-4/SN; ACEA E4/E6/E7/E8/E9/E11; MB 228.51, MB 228.52, MB 228.31; MAN 3677 / 3477 / 3271; VOLVO VDS 4.5; Mack EOS 4.5; DDC DFS 93K222; CAT ECF-3; DEUTZ DQC IV-18 LA; FORD WSS-M2C213-A; and RVI RLD-3.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. If it comes into contact with skin or eyes, the affected area should be washed thoroughly with soap and water, and medical assistance should be sought if necessary. In case of ingestion, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, ensure exposure to fresh air and seek medical help if required. Used Lubran motor oil should be collected in appropriate waste oil collection containers and delivered to authorized recycling centers in compliance with the applicable waste management regulations. It should not be disposed of in trash, sewage, or nature, and should not be mixed with any other petroleum product or chemical. Containers should not be thrown away or left in the environment but delivered to licensed recycling facilities. The product must not be burned in stoves or boilers. Keep out of the reach of children. For detailed information, please refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran motor oil packages should not be exposed to prolonged and direct sunlight. Packages should be kept away from dusty environments and must not be in contact with oils. The ambient temperature should not exceed 40°C. It is the sole responsibility of the user to ensure compliance with the intended use of the product and the relevant regulations in force. Lubran cannot be held liable for any damage, harm, or risks arising from improper use or use outside the intended purpose of the product.

TYPICAL CHARACTERISTICS

PHYSICAL PROPERTY	METHOD	5W-40 CK-4
Density, g/cm ³ at 15°C	ASTM D 4052	0,855
Kinematic Viscosity, cSt at 100°C	ASTM D 445	12,5-16,3
Viscosity Index, min.	ASTM D 2270	160
Pour Point, °C, max.	ASTM D 97	-40
Flash Point, °C, min.	ASTM D 92	220

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE