


## WELLIX EXTRA 10W-40



### SYNTHETIC HIGH-PERFORMANCE ENGINE OIL

#### DESCRIPTION AND APPLICATION

This motor oil is specially developed with synthetic technology to provide effective lubrication and protection. It is a synthetic engine oil designed for four-stroke gasoline, LPG, and diesel engines (non-DPF equipped), meeting the API SN/CF and ACEA A3/B4 specifications. It can be safely used in passenger cars and vans with turbocharged, direct injection, or non-injection engines year-round.

#### FEATURES AND BENEFITS

- Maintains its durable film strength and protection even under challenging operating conditions.
- Active cleaning properties control soot and sludge buildup, keeping the engine clean.
- High oxidation stability preserves its properties until the next oil change.
- Provides excellent protection against rust and wear with its special additive composition.
- High viscosity index ensures smooth engine operation in all seasons.

#### PERFORMANCE

Meets the performance requirements of: API SN/CF, ACEA A3/B4, MB 229.1/229.3, VW 502.00/505.00/501.01/500.00, RENAULT RN0700/0710, PSA B71 2294.

#### HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran engine oil should not come into contact with skin or eyes, should not be swallowed, and its vapors should not be inhaled. In case of contact with skin or eyes, rinse thoroughly with soap and water and seek medical attention if necessary. If swallowed, do not induce vomiting and seek emergency medical attention. If vapors are inhaled, take deep breaths and seek medical help if needed. Used Lubran engine oils must not be discharged into drains, sewers, or the environment. They should be collected in designated waste oil containers and delivered to authorized recycling centers in accordance with applicable regulations. They must not be mixed with other petroleum derivatives or chemicals and should not be burned in stoves or furnaces. Empty containers should not be disposed of in landfills or the environment but handed over to licensed recycling organizations. For detailed information, you can review the "Material Safety Data Sheet."

#### STORAGE CONDITIONS

Lubran engine oil packages should not be exposed to direct sunlight for extended periods. Packages must not come into contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. The ambient temperature should not exceed 40°C. The proper use of this product in compliance with current laws and regulations is the sole responsibility of the user. Lubran cannot be held liable for any damages or adverse effects resulting from improper use, deviations from the intended purpose, or the product's inherent hazards.

#### TYPICAL PROPERTIES

PHYSICAL PROPERTY	METHOD	WELLIX DPF 5W-40
Density, g/cm <sup>3</sup> at 15°C	ASTM D 4052	0,850
Kinematic Viscosity, cSt, 100°C	ASTM D 445	12,5-16,3
Viscosity Index	ASTM D 2270	160
Pour Point, °C, max	ASTM D 97	-39
Flash Point, °C, min	ASTM D 92	235

#### PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.  
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE