


WELLIX EXTRA 5W-30



HIGH-PERFORMANCE MOTOR OIL

DESCRIPTION AND APPLICATION

LUBRAN WELLIX EXTRA 5W-30 is a high-performance synthetic technology motor oil designed for use in both gasoline and diesel engine vehicles.

FEATURES AND BENEFITS

- Thanks to its new additive technology, it provides excellent protection against engine wear even under the most demanding operating conditions.
- Its high oxidation stability extends oil change intervals and preserves product performance.
- Outstanding fluidity at low temperatures ensures easy cold starts and rapid oil circulation in the engine during winter.
- Suitable for use in diesel and gasoline passenger cars as well as light commercial vehicles.
- Compatible with Diesel Particulate Filters (DPF) and all gasoline catalytic converters.
- Delivers long-lasting engine protection against wear, sludge, and deposits with excellent performance at both low and high temperatures.

PERFORMANS

Meets the requirements of API SN/CF; ACEA A3/B4; GM dexos2; MB 229.3 | MB 229.5 | MB 226.5 | VW 502 00 | VW 505 00 | BMW LL-01 | OPEL GM LL-A-025 | GM LL-B-025 | Renault RN 0700 / Renault RN 0710.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. If it comes into contact with skin or eyes, the affected area should be washed thoroughly with soap and water, and medical assistance should be sought if necessary. In case of ingestion, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, ensure exposure to fresh air and seek medical help if required. Used Lubran motor oil should be collected in appropriate waste oil collection containers and delivered to authorized recycling centers in compliance with the applicable waste management regulations. It should not be disposed of in trash, sewage, or nature, and should not be mixed with any other petroleum product or chemical. Containers should not be thrown away or left in the environment but delivered to licensed recycling facilities. The product must not be burned in stoves or boilers. Keep out of the reach of children. For detailed information, please refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran motor oil packages should not be exposed to prolonged and direct sunlight. Packages should be kept away from dusty environments and must not be in contact with oils. The ambient temperature should not exceed 40°C. It is the sole responsibility of the user to ensure compliance with the intended use of the product and the relevant regulations in force. Lubran cannot be held liable for any damage, harm, or risks arising from improper use or use outside the intended purpose of the product.

TYPICAL CHARACTERISTICS

PHYSICAL PROPERTY	METHOD	WELLIX EXTRA 5W-30
Density, g/cm ³ at 15°C	ASTM D 4052	0,860
Kinematic Viscosity, cSt at 100°C	ASTM D 445	9,3-12,5
Viscosity Index, min.	ASTM D 2270	150
Pour Point, °C, max.	ASTM D 97	-35
Flash Point, °C, min.	ASTM D 92	200

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE