


WELLIX EXTRA 5W-40



HIGH-PERFORMANCE SYNTHETIC MOTOR OILS

DESCRIPTION AND APPLICATION

It is a high-performance motor oil with synthetic technology, offering superior cleaning and protection properties. Provides excellent cold start performance and high-temperature protection. Thanks to its engine cleaning and wear prevention features, it offers extended oil change intervals.

FEATURES AND BENEFITS

- Thanks to its new additive technology, it provides excellent protection against potential engine wear even under the most demanding operating conditions.
- Its enhanced friction-reducing properties contribute to improved fuel economy.
- High oxidation stability helps maintain oil performance until the next oil change.
- Low volatility reduces oil consumption.

PERFORMANCE

Meets the performance specifications of API SN/CF; ACEA A3/B4; MB 229.3, 229.5, 226.5; VW 502.00 / 505.00; Fiat 9.55535-H2 / M2 / N2 / Z2; Opel GM LL-B-025 (diesel); RN 0710, and RN 0700.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. If it comes into contact with skin or eyes, the affected area should be washed thoroughly with soap and water, and medical assistance should be sought if necessary. In case of ingestion, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, ensure exposure to fresh air and seek medical help if required. Used Lubran motor oil should be collected in appropriate waste oil collection containers and delivered to authorized recycling centers in compliance with the applicable waste management regulations. It should not be disposed of in trash, sewage, or nature, and should not be mixed with any other petroleum product or chemical. Containers should not be thrown away or left in the environment but delivered to licensed recycling facilities. The product must not be burned in stoves or boilers. Keep out of the reach of children. For detailed information, please refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran motor oil packages should not be exposed to prolonged and direct sunlight. Packages should be kept away from dusty environments and must not be in contact with oils. The ambient temperature should not exceed 40°C. It is the sole responsibility of the user to ensure compliance with the intended use of the product and the relevant regulations in force. Lubran cannot be held liable for any damage, harm, or risks arising from improper use or use outside the intended purpose of the product.

TYPICAL CHARACTERISTICS

PHYSICAL PROPERTY	METHOD	WELLIX EXTRA 5W-40
Density, g/cm ³ at 15°C	ASTM D 4052	0,850
Kinematic Viscosity, cSt at 100°C	ASTM D 445	12,5-16,3
Viscosity Index, min.	ASTM D 2270	160
Pour Point, °C, max.	ASTM D 97	-39
Flash Point, °C, min.	ASTM D 92	235

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE