

MOTOJET 2T



2-Stroke Motorcycle Oils

DESCRIPTION AND APPLICATION

This 2-stroke engine oil is produced by blending high-quality mineral base oils with premium performance additives. It is used in all gasoline-powered 2-stroke motorcycles, garden machinery, engines, and test engines.

FEATURES AND BENEFITS

- Provides excellent lubrication, preventing wear on the crankshaft and piston rod.
- Its high-quality additives provide superior protection against wear, extending engine life.
- Keeps the engine clean, prolonging the life of valves and spark plugs while reducing the risk of piston seizure.
- Provides excellent protection against rust and corrosion, extending the life of metal parts.
- Ensures efficient operation of the ignition system, maintaining maximum performance.
- Easily mixes with gasoline, ensuring compatibility.

PERFORMANCE

Meets the performance requirements of API TC and JASO FC.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with eyes, be ingested, or inhaled. If contact occurs with the skin or eyes, wash thoroughly with soap and water, and seek medical assistance. In case of inhalation, move to fresh air and seek medical attention. If swallowed, do not induce vomiting and immediately seek medical help. Used Lubran motor oil should not be disposed of via regular trash, drainage systems, or unauthorized collection points. Waste oil must be delivered to designated collection facilities. Do not burn any petroleum product or mix it with chemicals. Keep out of reach of children. Empty containers should not be reused and must be disposed of properly. For detailed information, please refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran motor oils should not be exposed to direct sunlight for extended periods. Containers should be kept in clean and dust-free environments. Avoid storing the product at temperatures exceeding 40°C. It is recommended to use the product within the timeframe specified by the manufacturer. Lubran is not responsible for any damages resulting from improper storage conditions or negligence.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	Motojet 2T
Density, g/cm ³ at 15°C	ASTM D 4052	0,879
Kinematic Viscosity, cSt, 100°C	ASTM D 445	9,4-11,4
Viscosity Index, min	ASTM D 2270	98
Pour Point, °C, max	ASTM D 97	-12
Flash Point, °C, min	ASTM D 92	230

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE