


## PROLUBE 15W-40



### SEMI-SYNTHETIC HIGH-PERFORMANCE ENGINE OILS

#### DESCRIPTION AND APPLICATION

LUBRAN PROLUBE 15W-40 API CG-4/SJ is a high-performance semi-synthetic motor oil developed for heavy-duty diesel and gasoline engines. Thanks to its semi-synthetic formulation, it protects your engine against wear, deposits, and corrosion, keeping it clean and efficient. Maintains its viscosity even under tough operating conditions, ensuring smooth engine performance. Delivers superior performance and long-lasting use in naturally aspirated, turbocharged, and catalytic converter-equipped engines.

#### FEATURES AND BENEFITS

- Provides high oxidation resistance. Prevents rust and corrosion, offering excellent protection against engine wear.
- Its high TBN value prevents acid formation, ensuring superior protection and extended oil life, contributing to cost savings.
- Thanks to the detergent-dispersant properties of its additives, it prevents sludge and deposit formation, keeping the engine clean.
- Its high viscosity index ensures excellent protection throughout all seasons.
- Contains anti-foam additives for more effective lubrication.
- Helps reduce exhaust emissions and contributes to air pollution prevention.
- Delivers superior protection and oil consumption control under all climate and road conditions.

#### PERFORMANCE

Meets the performance specifications of API CG-4/SJ, ACEA E3-96/83-96/A2-96, MB 228.1 / 228.3, VW 501.01 / 505.00, MAN 271 / 3275, and Volvo VDS / VDS-2.

#### HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. If it comes into contact with skin or eyes, the affected area should be washed thoroughly with soap and water, and medical assistance should be sought if necessary. In case of ingestion, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, ensure exposure to fresh air and seek medical help if required. Used Lubran motor oil should be collected in appropriate waste oil collection containers and delivered to authorized recycling centers in compliance with the applicable waste management regulations. It should not be disposed of in trash, sewage, or nature, and should not be mixed with any other petroleum product or chemical. Containers should not be thrown away or left in the environment but delivered to licensed recycling facilities. The product must not be burned in stoves or boilers. Keep out of the reach of children. For detailed information, please refer to the "Material Safety Data Sheet."

#### STORAGE CONDITIONS

Lubran motor oil packages should not be exposed to prolonged and direct sunlight. Packages should be kept away from dusty environments and must not be in contact with oils. The ambient temperature should not exceed 40°C. It is the sole responsibility of the user to ensure compliance with the intended use of the product and the relevant regulations in force. Lubran cannot be held liable for any damage, harm, or risks arising from improper use or use outside the intended purpose of the product.

#### TYPICAL CHARACTERISTICS

PHYSICAL PROPERTY	METHOD	PROLUBE 15W-40
Density, g/cm <sup>3</sup> at 15°C	ASTM D 4052	0,870
Kinematic Viscosity, cSt at 100°C	ASTM D 445	12,5-16,3
Viscosity Index, min.	ASTM D 2270	140
Pour Point, °C, max.	ASTM D 97	-36
Flash Point, °C, min.	ASTM D 92	225

#### PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.  
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE