

WELLIX DPF 5W-30



High-Performance Synthetic Engine Oils

DESCRIPTION AND APPLICATION

This advanced synthetic engine oil, developed with LOW SAPS technology, is specially designed to meet the requirements of vehicles equipped with new-generation DPF systems. WELLIX DPF 5W-30 is recommended for high-performance gasoline and diesel engines, especially for modern passenger cars, SUVs, and light commercial vehicles.

FEATURES AND BENEFITS

- Provides excellent protection against potential wear in the engine under harsh operating conditions, thanks to its advanced additive technology.
- Offers exceptional cleaning properties.
- Provides fuel economy thanks to its enhanced anti-friction properties.
- Maintains its properties until the next oil change due to its high oxidation stability.
- Reduces oil consumption thanks to its low volatility.
- Demonstrates extra performance compared to conventional engine oils.
- Provides excellent performance in DPF-equipped vehicles due to its low ash content.

PERFORMANCE

Recommended for vehicles requiring API: SN/CF ACEA C2/C3; GM dexos2; MB 229.31; MB 229.51; MB 229.52 BMW LL-04; RN 0700/0710; Porsche C30; VW 504.00/507.01.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran engine oil should not come into contact with skin or eyes, should not be swallowed, and its vapors should not be inhaled. In case of contact with skin or eyes, rinse thoroughly with soap and water and seek medical attention if necessary. If swallowed, do not induce vomiting and seek emergency medical attention. If vapors are inhaled, take deep breaths and seek medical help if needed. Used Lubran engine oils must not be discharged into drains, sewers, or the environment. They should be collected in designated waste oil containers and delivered to authorized recycling centers in accordance with the applicable regulations. They must not be mixed with other petroleum derivatives or chemicals and should not be burned in stoves or furnaces. Empty containers should not be disposed of in landfills or the environment but handed over to licensed recycling organizations. For detailed information, you can review the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran engine oil packages should not be exposed to direct sunlight for extended periods. Packages must not come into contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. The ambient temperature should not exceed 40°C. The proper use of this product in compliance with current laws and regulations is the sole responsibility of the user. Lubran cannot be held liable for any damages or adverse effects resulting from improper use or deviations from the intended purpose or the product's inherent hazards.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	WELLIX DPF 5W-30
Density, g/cm ³ at 15°C	ASTM D 4052	0,850
Kinematic Viscosity, cSt, 100°C	ASTM D 445	9,3-12,6
Viscosity Index, min	ASTM D 2270	165
Pour Point, °C, max	ASTM D 97	-42
Flash Point, °C, min	ASTM D 92	230

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE