

## WELLIX EXTRA 10W-40



### SYNTHETIC-BASED HIGH-PERFORMANCE MOTOR OIL

#### DESCRIPTION AND APPLICATION

A passenger car and light commercial engine oil specially developed with synthetic technology to provide excellent protection and effective lubrication under all climate conditions. Suitable for use in gasoline or diesel engines of passenger cars and light commercial vehicles.

#### FEATURES AND BENEFITS

- Maintains stable film strength even under harsh operating conditions without losing its protective properties.
- Its active cleaning feature controls deposit and sludge formation, keeping the engine clean.
- High oxidation stability ensures the oil retains its properties until the next oil change.
- Contains special additives that protect the engine against corrosion and wear.
- Delivers superior performance compared to conventional motor oils.
- Its high viscosity index ensures smooth engine operation.

#### PERFORMANCE

Meets the performance specifications of API SL/CF, ACEA A3/B4, MB 229.1 / 229.3, and VW 501.01 / 505.00.

#### HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. If it comes into contact with skin or eyes, the affected area should be washed thoroughly with soap and water, and medical assistance should be sought if necessary. In case of ingestion, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, ensure exposure to fresh air and seek medical help if required. Used Lubran motor oil should be collected in appropriate waste oil collection containers and delivered to authorized recycling centers in compliance with the applicable waste management regulations. It should not be disposed of in trash, sewage, or nature, and should not be mixed with any other petroleum product or chemical. Containers should not be thrown away or left in the environment but delivered to licensed recycling facilities. The product must not be burned in stoves or boilers. Keep out of the reach of children. For detailed information, please refer to the "Material Safety Data Sheet."

#### STORAGE CONDITIONS

Lubran motor oil packages should not be exposed to prolonged and direct sunlight. Packages should be kept away from dusty environments and must not be in contact with oils. The ambient temperature should not exceed 40°C. It is the sole responsibility of the user to ensure compliance with the intended use of the product and the relevant regulations in force. Lubran cannot be held liable for any damage, harm, or risks arising from improper use or use outside the intended purpose of the product.

#### TYPICAL CHARACTERISTICS

PHYSICAL PROPERTY	METHOD	WELLIX EXTRA 10W-40
Density, g/cm <sup>3</sup> at 15°C	ASTM D 4052	0,865
Kinematic Viscosity, cSt at 100°C	ASTM D 445	12,5-16,3
Viscosity Index, min.	ASTM D 2270	150
Pour Point, °C, max.	ASTM D 97	-39
Flash Point, °C, min.	ASTM D 92	220

#### PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.  
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE