

## LUBRAN GREASE LITHIUM EP 1-2-3

### DEFINITION AND APPLICATION

It is a multi-purpose lithium soap grease containing extreme pressure additive EP. It can be used easily in heavy and shock load applications. It provides high protection and excellent resistance to heat, especially for high speed and water environments. It is recommended for the lubrication of wide roller bearings in dry and wet ends of machines. It can operate between -12 and 130°C.

### FEATURES AND BENEFITS

- It provides very good protection against heavy and impact loads with its high overpressure prevention feature.
- It extends bearing life by reducing wear and fatigue.
- It provides savings by helping to reduce grease consumption.
- It reduces maintenance and labor costs.
- It is easily pumped in central systems.
- It provides excellent protection against rust and corrosion.

### PERFORMANCE

Meets DIN 51825 performance specifications.

### HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran grease oil should be kept away from skin and eyes and should not be ingested or inhaled. In case of contact with skin or eyes, wash immediately with soapy water. If swallowed, seek medical attention. In case of vapor inhalation, move to fresh air and consult a doctor if necessary. Used oil must be disposed of in compliance with local regulations. Avoid releasing used oil into the environment. Empty containers must not be reused or burned. Keep out of reach of children and store in properly ventilated places. For more detailed information, refer to the "Material Safety Data Sheet."

### STORAGE CONDITIONS

Lubran grease oil containers should not be exposed to direct sunlight for extended periods. Containers should be stored in environments with temperatures not exceeding 40°C. Protect from physical damage and contamination. Use the product in accordance with its intended purpose to maintain its quality and ensure safe use.

### TYPICAL PROPERTIES

PHYSICAL PROPERTIES	1	2	3
Soap Type	Li	Li	Li
Processed Penetration/	310/340	265/295	220/250
Dropping Point °C /	185	185	185

### PACKAGING TYPES

