


MONOGRADE SAE 30



High-Quality Monograde Oil

DESCRIPTION AND APPLICATION

Highly refined, high-viscosity index, low-carbon, paraffinic base non-additive motor oils. Safely used in all recommended applications for non-additive oils.

FEATURES AND BENEFITS

- Non-additive oils are used in all recommended applications.
- High oxidation and thermal stability.
- Increases engine power and fuel efficiency while reducing maintenance and operating costs.
- High viscosity indices. Forms an excellent film layer to protect the engine against wear.
- Economical for use under light conditions.

PERFORMANCE

Meets API CA/SA performance specifications.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be swallowed, and its vapors should not be inhaled. In case of contact with skin or eyes, rinse thoroughly with soap and water and seek medical attention if necessary. If swallowed, do not induce vomiting and seek emergency medical attention. If vapors are inhaled, take deep breaths and seek medical help if needed. Used Lubran oils must not be discharged into drains, sewers, or the environment. They should be collected in designated waste oil containers and delivered to authorized recycling centers in accordance with applicable regulations. They must not be mixed with other petroleum derivatives or chemicals and should not be burned in stoves or furnaces. Empty containers should not be disposed of in landfills or the environment but handed over to licensed recycling organizations. For detailed information, you can review the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran oil packages should not be exposed to direct sunlight for extended periods. Packages must not come into contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. The ambient temperature should not exceed 40°C. The proper use of this product in compliance with current laws and regulations is the sole responsibility of the user. Lubran cannot be held liable for any damages or adverse effects resulting from improper use, deviations from the intended purpose, or the product's inherent hazards.

TYPICAL PROPERTIES

PHYSICAL PROPERTY	METHOD	SAE 30
Density, g/cm ³ at 15°C	ASTM D 4052	0,885
Kinematic Viscosity, cSt, 100°C	ASTM D 445	9,4-11,4
Viscosity Index	ASTM D 2270	95
Pour Point, °C, max	ASTM D 97	-9
Flash Point, °C, min	ASTM D 92	230

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE