

MONOGRADE SAE 60



High-Quality Monograde Oil

DESCRIPTION AND APPLICATION

Monograde oil is suitable for certain gasoline and diesel engines that do not require high performance or advanced engine oils and are subject to specific demands beyond standard requirements.

FEATURES AND BENEFITS

- Recommended for use in all applications requiring additive-free oil.
- Offers high oxidation and thermal stability.
- Improves engine power and fuel efficiency, reducing maintenance and operating costs.
- Features high viscosity indices and creates an excellent film layer that protects the engine from wear.
- Economical for light-duty conditions.

PERFORMANCE

Meets API CA/SA performance standards.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with the skin or eyes, should not be ingested, and its vapor should not be inhaled. If contact occurs, wash thoroughly with soap and water; seek immediate medical attention if necessary. Vapors should be avoided; if inhaled, move to fresh air and seek help. Used Lubran motor oil must be disposed of legally and through authorized waste oil collection centers. Do not mix with other substances. Empty containers must not be discarded in the environment. Refer to the "Material Safety Data Sheet" for more details.


STORAGE CONDITIONS

Lubran motor oil packages should be stored away from prolonged exposure to direct sunlight. The packaging should remain sealed and be stored in a dust-free environment at temperatures below 40°C. Users are responsible for following all applicable laws and regulations for usage.

TYPICAL PROPERTIES

PHYSICAL PROPERTY	METHOD	SAE 60
Density, g/cm ³ at 15°C	ASTM D 4052	0,889
Kinematic Viscosity, cSt, 100°C	ASTM D 445	21,9-26,1
Viscosity Index	ASTM D 2270	110
Pour Point, °C, max	ASTM D 97	-16
Flash Point, °C, min	ASTM D 92	230

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE