


RACELUBE 10W-60



HIGH-PERFORMANCE ENGINE OILS

DESCRIPTION AND APPLICATION

Lubran Racelube 10W-60 is a high-performance engine oil formulated with state-of-the-art additive packages and synthetic base oils to enhance the torque, power, and efficiency of sports and high-powered engines. It is specially designed for gasoline and diesel engines operating under high stress and is suitable for a wide range of engine types, including 4-stroke gasoline engines, multi-valve engines, turbocharged and naturally aspirated 4-stroke diesel engines. Its high-performance formula provides an extremely durable lubrication film that resists pressure. The special formulation ensures effective engine cleaning, superior wear protection, and noticeable fuel economy.

FEATURES AND BENEFITS

- Ensures smooth lubrication exactly when engine performance demands it most.
- Its superior thermal and oxidation stability maintains performance throughout the extended oil drain intervals recommended by engine manufacturers.
- Helps prevent oil leaks and supports effective sealing.
- Cleans the engine internally and helps remove existing deposits and sludge.
- Provides excellent wear protection with additives included in its formulation.
- Its high viscosity helps minimize oil burning in older engines.

PERFORMANCE

Meets the performance specifications of API SP and ACEA A3/B4.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. If it comes into contact with skin or eyes, the affected area should be washed thoroughly with soap and water, and medical assistance should be sought if necessary. In case of ingestion, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, ensure exposure to fresh air and seek medical help if required. Used Lubran motor oil should be collected in appropriate waste oil collection containers and delivered to authorized recycling centers in compliance with the applicable waste management regulations. It should not be disposed of in trash, sewage, or nature, and should not be mixed with any other petroleum product or chemical. Containers should not be thrown away or left in the environment but delivered to licensed recycling facilities. The product must not be burned in stoves or boilers. Keep out of the reach of children. For detailed information, please refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran motor oil packages should not be exposed to prolonged and direct sunlight. Packages should be kept away from dusty environments and must not be in contact with oils. The ambient temperature should not exceed 40°C. It is the sole responsibility of the user to ensure compliance with the intended use of the product and the relevant regulations in force. Lubran cannot be held liable for any damage, harm, or risks arising from improper use or use outside the intended purpose of the product.

TYPICAL CHARACTERISTICS

PHYSICAL PROPERTY	METHOD	RACELUBE 10W-60
Density, g/cm ³ at 15°C	ASTM D 4052	0,860
Kinematic Viscosity, cSt at 100°C	ASTM D 445	21,9-26,1
Viscosity Index, min.	ASTM D 2270	155
Pour Point, °C, max.	ASTM D 97	-37
Flash Point, °C, min.	ASTM D 92	230

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE