


WELLIX HYBRID 0W-16



HIGH-PERFORMANCE SYNTHETIC MOTOR OILS

DESCRIPTION AND APPLICATION

Formulated with synthetic base oils, it offers excellent protection for your engine through its high shear stability, superior wear protection, engine cleanliness, and optimal thermal stability. It is a high-performance synthetic motor oil specially developed for use in new-generation hybrid electric vehicles (HEVs) and plug-in hybrid electric vehicles (PHEVs). Provides rapid lubrication in vehicles equipped with start-stop technology. Protects against Low-Speed Pre-Ignition (LSPi). Helps reduce both oil and fuel consumption.

FEATURES AND BENEFITS

- Ensures optimal oil pressure under all operating conditions.
- Provides smooth engine start-up and immediate lubrication after cold starts, protecting the engine against wear.
- Delivers excellent performance at both high and low temperatures.
- Offers outstanding engine cleanliness and wear resistance.
- Low volatility reduces oil consumption.
- Contributes to fuel savings and helps reduce pollutant emissions.

PERFORMANCE

Recommended for use in vehicles requiring API SP (RC), ILSAC GF-6B specifications, including TOYOTA, SUZUKI, NISSAN, CHERY, KIA, HONDA, and LEXUS.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. If it comes into contact with skin or eyes, the affected area should be washed thoroughly with soap and water, and medical assistance should be sought if necessary. In case of ingestion, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, ensure exposure to fresh air and seek medical help if required. Used Lubran motor oil should be collected in appropriate waste oil collection containers and delivered to authorized recycling centers in compliance with the applicable waste management regulations. It should not be disposed of in trash, sewage, or nature, and should not be mixed with any other petroleum product or chemical. Containers should not be thrown away or left in the environment but delivered to licensed recycling facilities. The product must not be burned in stoves or boilers. Keep out of the reach of children. For detailed information, please refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran motor oil packages should not be exposed to prolonged and direct sunlight. Packages should be kept away from dusty environments and must not be in contact with oils. The ambient temperature should not exceed 40°C. It is the sole responsibility of the user to ensure compliance with the intended use of the product and the relevant regulations in force. Lubran cannot be held liable for any damage, harm, or risks arising from improper use or use outside the intended purpose of the product.

TYPICAL CHARACTERISTICS

PHYSICAL PROPERTY	METHOD	WELLIX 0W-16
Density, g/cm ³ at 15°C	ASTM D 4052	0,845
Kinematic Viscosity, cSt at 100°C	ASTM D 445	6,1-8,2
Viscosity Index, min.	ASTM D 2270	155
Pour Point, °C, max.	ASTM D 97	-40
Flash Point, °C, min.	ASTM D 92	210

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE