


WELLIX HYBRID 0W-8



HIGH-PERFORMANCE SYNTHETIC MOTOR OILS

DESCRIPTION AND APPLICATION

Formulated with synthetic base oils, it provides excellent engine protection through its wear-resistant properties, high shear stability, optimal thermal stability, and ability to keep the engine clean. It is a fully synthetic, ultra-low viscosity motor oil specially developed to meet the high demands of gasoline hybrid engines. Thanks to its state-of-the-art additive package, it ensures minimal oil and fuel consumption while delivering maximum engine efficiency.

FEATURES AND BENEFITS

- Ensures optimal oil pressure under all operating conditions.
- Provides smooth engine start-up and immediate lubrication after cold starts, protecting the engine from wear.
- Delivers superior performance at both high and low temperatures.
- Maintains excellent engine cleanliness and wear resistance.
- Its low volatility reduces oil consumption.
- Contributes to fuel savings and lowers pollutant emissions.

PERFORMANCE

Meets the performance specifications of API SP, ILSAC GF-6B, JASO GLV-1, as well as TOYOTA and MAZDA.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. If it comes into contact with skin or eyes, the affected area should be washed thoroughly with soap and water, and medical assistance should be sought if necessary. In case of ingestion, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, ensure exposure to fresh air and seek medical help if required. Used Lubran motor oil should be collected in appropriate waste oil collection containers and delivered to authorized recycling centers in compliance with the applicable waste management regulations. It should not be disposed of in trash, sewage, or nature, and should not be mixed with any other petroleum product or chemical. Containers should not be thrown away or left in the environment but delivered to licensed recycling facilities. The product must not be burned in stoves or boilers. Keep out of the reach of children. For detailed information, please refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran motor oil packages should not be exposed to prolonged and direct sunlight. Packages should be kept away from dusty environments and must not be in contact with oils. The ambient temperature should not exceed 40°C. It is the sole responsibility of the user to ensure compliance with the intended use of the product and the relevant regulations in force. Lubran cannot be held liable for any damage, harm, or risks arising from improper use or use outside the intended purpose of the product.

TYPICAL CHARACTERISTICS

PHYSICAL PROPERTY	METHOD	WELLIX 0W-8
Density, g/cm ³ at 15°C	ASTM D 4052	0,845
Kinematic Viscosity, cSt at 100°C	ASTM D 445	4,0-6,1
Viscosity Index, min.	ASTM D 2270	150
Pour Point, °C, max.	ASTM D 97	-40
Flash Point, °C, min.	ASTM D 92	200

AMBALAJ TIPLERİ



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE