

GEARLUBE FULLTRANS EP 75W-90



Heavy-Duty Transmission and Differential Synthetic Gear Oil

DESCRIPTION AND APPLICATION

GearLube Fulltrans EP 75W-90 is a fully synthetic heavy-duty gear oil with high performance and extended drain intervals. It is particularly suitable for modern passenger cars, commercial vehicles, off-road vehicles, and machinery operating under extreme conditions. It is safely used in synchronized or non-synchronized manual gearboxes, differentials, and transmission axles.

FEATURES AND BENEFITS

- Provides excellent protection for gear systems against wear, thanks to its EP additives and oil film under all temperatures and cold start conditions.
- High viscosity index ensures smooth gear shifting and superior performance even in cold weather conditions.
- Exhibits thermal stability and high oxidation resistance, ensuring extended service life.
- Prevents corrosion, foaming, and sludge formation, maintaining system cleanliness and efficiency.
- High performance increases oil change intervals and optimizes operational efficiency.

PERFORMANCE

Meets the following performance specifications: API GL-5; MT-1; MAN 341 Type E-3; MAN 341 Type GA-2; MAN 342 Type S1; ZF TE-ML 05A, 12L, 12N, 16F, 17B, 19C, 21A; DAF; MACK GO-J; VOLVO 97312.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran gear oil should be kept away from skin and eyes and should not be ingested or inhaled. In case of contact with skin or eyes, wash immediately with soapy water. If swallowed, seek medical attention. In case of vapor inhalation, move to fresh air and consult a doctor if necessary. Used oil must be disposed of in compliance with local regulations. Avoid releasing used oil into the environment. Empty containers must not be reused or burned. Keep out of reach of children and store in properly ventilated places. For more detailed information, refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran gear oil containers should not be exposed to direct sunlight for extended periods. Containers should be stored in environments with temperatures not exceeding 40°C. Protect from physical damage and contamination. Use the product in accordance with its intended purpose to maintain its quality and ensure safe use.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	EP 75W-90
Density, g/cm ³ at 15°C	ASTM D 4052	0,862
Kinematic Viscosity, cSt, at 100°C	ASTM D 445	13,5-16,5
Viscosity Index	ASTM D 2270	145
Pour Point, °C	ASTM D 97	-42
Flash Point, °C	ASTM D 92	200

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE