


## PROLUBE 15W-40 CF-4 / SL



### High-Performance Motor Oils

#### DESCRIPTION AND APPLICATION

LUBRAN PROLUBE 15W-40 CF-4 / SL is a high-performance multigrade motor oil suitable for year-round use. It is formulated by blending mineral-based oils with premium-quality additives. It is suitable for use in passenger cars with atmospheric or turbocharged engines, as well as in heavy-duty commercial vehicles, buses, trucks, tractors, agricultural, and construction machinery powered by diesel and gasoline engines.

#### FEATURES AND BENEFITS

- High oxidation resistance. Prevents corrosion and wear, providing excellent protection against engine wear.
- The high TBN value prevents the formation of acidic substances, offering superior protection. Extends the oil's service life, ensuring cost efficiency.
- Detergent-dispersant additives help prevent deposits and sludge formation, keeping the engine clean.
- High viscosity index ensures excellent performance under all operating conditions.
- Contains foam inhibitors, providing better lubrication.
- Reduces exhaust gas emissions, preventing air pollution.
- Provides superior protection and control of oil consumption in all climates and working conditions.

#### PERFORMANCE

Meets the performance requirements of: API CF-4/CF/CG-4/SL/SH/SG; ACEA B2, ACEA E3; MIL-L-2104 D; MB 228.3; MAN-3275; Volvo VDS-2; MTU DDC Type 2 Mack EO-N, Mack EO-M Plus, RENAULT TRUCKS RLD-2, VOLVO VDS-3.

#### HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with eyes, be ingested, or inhaled. If contact occurs with the skin or eyes, wash thoroughly with soap and water and seek medical assistance. In case of inhalation, move to fresh air and seek medical attention. If swallowed, do not induce vomiting and immediately seek medical help. Used Lubran motor oil should not be disposed of via regular trash, drainage systems, or collection points that are not compliant with local regulations. Waste oil should be delivered to authorized collection facilities. Do not burn any petroleum product or mix it with chemicals. Keep out of reach of children. Do not reuse empty containers for storage; dispose of them properly. For detailed information, please review the "Material Safety Data Sheet."


#### STORAGE CONDITIONS

Lubran motor oils should not be exposed to direct sunlight for prolonged periods. Containers should be kept clean and protected from dust. Avoid storing at temperatures exceeding 40°C. It is recommended to use the product within the specified time frame provided by the manufacturer. Lubran is not responsible for any damages resulting from improper storage or use beyond the intended purpose of the product.

#### TYPICAL PROPERTIES

| PHYSICAL PROPERTIES                | METHOD      | PROLUBE 15W-40 |
|------------------------------------|-------------|----------------|
| Density, g/cm <sup>3</sup> at 15°C | ASTM D 4052 | 0,870          |
| Kinematic Viscosity, cSt, 100°C    | ASTM D 445  | 12,5-16,3      |
| Viscosity Index, min               | ASTM D 2270 | 140            |
| Pour Point, °C, max                | ASTM D 97   | -36            |
| Flash Point, °C, min               | ASTM D 2270 | 225            |

#### PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.  
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE