

## GEARLUBE 140



### High-Quality Monograde Gear Oil

#### DESCRIPTION AND APPLICATION

GearLube 140 is a high-quality mineral-based oil designed for use in automotive and industrial equipment gearboxes and differentials that do not require extreme pressure additives. It is suitable for manual transmissions and differentials operating under light loads.

#### FEATURES AND BENEFITS

- Provides superior protection against rust and corrosion.
- Its sealing feature ensures economic savings by preventing leakage.
- Extends the life of sealing elements and gaskets.
- Resists thermal stability and oxidation; maintains high performance in gear systems.
- Offers economical use in light-load conditions.

#### PERFORMANCE

Meets API GL-1 performance specifications.

#### HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran gear oil should be kept away from skin and eyes and should not be ingested or inhaled. In case of contact with skin or eyes, wash immediately with soapy water. If swallowed, seek medical attention. In case of vapor inhalation, remove the person to fresh air and seek medical advice if necessary. Used gear oil must be disposed of in compliance with local regulations. Avoid disposing of used oil into the environment. Empty containers must not be reused or burned. Store the product away from children and in properly ventilated places. For further information, refer to the "Material Safety Data Sheet."

#### STORAGE CONDITIONS

Lubran gear oil containers should not be exposed to direct sunlight for extended periods. Containers should be stored in environments with temperatures not exceeding 40°C. Protect from physical damage and contamination. Use the product in accordance with its intended purpose and ensure proper storage to maintain quality.

#### TYPICAL PROPERTIES

| PHYSICAL PROPERTIES                | METHOD      | GEARLUBE 140 |
|------------------------------------|-------------|--------------|
| Density, g/cm <sup>3</sup> at 15°C | ASTM D 4052 | 0,889        |
| Kinematic Viscosity, cSt, at 100°C | ASTM D 445  | 26,5-32,5    |
| Viscosity Index                    | ASTM D 2270 | 95           |
| Pour Point, °C                     | ASTM D 97   | -12          |
| Flash Point, °C                    | ASTM D 92   | 230          |

#### PACKAGING TYPES

