

GEARLUBE EP 75W



High-Performance Fully Synthetic Monograde Transmission Oil

DESCRIPTION AND APPLICATION

LUBRAN GEARLUBE EP 75W, meeting API GL-5 performance standards, is a fully synthetic transmission oil recommended for use in most passenger vehicles with traditional dry clutch manual transmissions.

FEATURES AND BENEFITS

- Provides additional protection in very cold weather and improves gear-shifting quality.
- Excellent wear resistance ensures long-lasting performance.
- High thermal stability and superior cleanliness extend the lifespan of transmissions.
- Fully synthetic formulation offers excellent protection against wear, ensuring smooth gear operations.
- Special additive formulation reduces noise and improves driving comfort.
- High economic value.

PERFORMANCE

Meets API GL-5 performance specifications.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran gear oil should be kept away from skin and eyes and should not be ingested or inhaled. In case of contact with skin or eyes, wash immediately with soapy water. If swallowed, seek medical attention. In case of vapor inhalation, move to fresh air and consult a doctor if necessary. Used oil must be disposed of in compliance with local regulations. Avoid releasing used oil into the environment. Empty containers must not be reused or burned. Keep out of reach of children and store in properly ventilated places. For more detailed information, refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran gear oil containers should not be exposed to direct sunlight for extended periods. Containers should be stored in environments with temperatures not exceeding 40°C. Protect from physical damage and contamination. Use the product in accordance with its intended purpose to maintain its quality and ensure safe use.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	GEARLUBE EP 75W
Density, g/cm ³ at 15°C	ASTM D 4052	0,850
Kinematic Viscosity, cSt, at 100°C	ASTM D 445	4,2-6,9
Viscosity Index	ASTM D 2270	130
Pour Point, °C	ASTM D 97	-42
Flash Point, °C	ASTM D 92	210

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE