

ATF



Hydraulic Steering Oil



Tüm Araçlar



Mineral

Hydraulic Steering Oil

DESCRIPTION AND APPLICATION

This high-performance hydraulic steering oil is produced by blending high-quality base oils and superior-quality additives. It is suitable for use in hydraulic steering systems of all vehicles.

FEATURES AND BENEFITS

- Protects the system against rust and corrosion.
- Reduces friction within the system due to a wide working temperature range.
- Ensures the system operates smoothly, silently, and efficiently.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with the skin or eyes, should not be ingested, and its vapor should not be inhaled. If contact occurs, wash the affected area thoroughly with soap and water and seek immediate medical attention if needed. Vapors should be avoided; if inhaled, move to fresh air and seek medical assistance. Used Lubran motor oils must be collected in waste oil tanks and disposed of at authorized recycling centers. Do not mix with other substances. Empty containers should not be discarded in the environment. Refer to the "Material Safety Data Sheet" for more details.

STORAGE CONDITIONS

Lubran motor oil packages should not be exposed to prolonged direct sunlight. Packaging must remain sealed and stored in a dust-free environment at temperatures below 40°C. Users are responsible for following all applicable laws and regulations regarding usage. Ensure the product is used for its intended purpose to prevent risks associated with improper use.

TYPICAL PROPERTIES

PHYSICAL PROPERTY	METHOD	ATF
Density, g/cm ³ at 15°C	ASTM D 4052	0,860-,870
Kinematic Viscosity, cSt, 100°C	ASTM D 445	5-6
Viscosity Index	ASTM D 2270	95
Pour Point, °C, max	ASTM D 97	-18
Flash Point, °C, min	ASTM D 92	210

PACKAGING TYPES

