

MOTOJET 4T 10W-40



4-Stroke Motorcycle Oils

DESCRIPTION AND APPLICATION

This high-performance, semi-synthetic motorcycle oil is produced by blending high-quality mineral base oils with premium performance additives. It can be safely used in 4-stroke motorcycles.

FEATURES AND BENEFITS

- Its effective formula creates a durable protective film layer on the engine and gearbox surfaces.
- Helps prevent wear, extending engine life and reducing maintenance costs.
- Contains oxidation-preventing additives, providing stability and reducing oil degradation over time.
- Protects against rust and corrosion, extending the life of metal parts.
- Its high viscosity index and thermal stability ensure excellent engine protection under both high and low temperatures.
- Detergent properties prevent sludge and deposit formation, keeping the engine clean.
- Prevents performance losses caused by frequent starts and stops, ensuring high engine durability and fuel efficiency.
- Delivers maximum performance for motorcycles.

PERFORMANCE

Meets the performance requirements of API SL and JASO MA.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with eyes, be ingested, or inhaled. If contact occurs with the skin or eyes, wash thoroughly with soap and water, and seek medical assistance. In case of inhalation, move to fresh air and seek medical attention. If swallowed, do not induce vomiting and immediately seek medical help. Used Lubran motor oil should not be disposed of via regular trash, drainage systems, or unauthorized collection points. Waste oil must be delivered to designated collection facilities. Do not burn any petroleum product or mix it with chemicals. Keep out of reach of children. Empty containers should not be reused and must be disposed of properly. For detailed information, please refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran motor oils should not be exposed to direct sunlight for extended periods. Containers should be kept in clean and dust-free environments. Avoid storing the product at temperatures exceeding 40°C. It is recommended to use the product within the timeframe specified by the manufacturer. Lubran is not responsible for any damages resulting from improper storage conditions or negligence.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	4T 10W-40
Density, g/cm ³ at 15°C	ASTM D 4052	0,870
Kinematic Viscosity, cSt, 100°C	ASTM D 445	12,5-16,3
Viscosity Index, min	ASTM D 2270	130
Pour Point, °C, max	ASTM D 97	-27
Flash Point, °C, min	ASTM D 92	210

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE