



ATF MULTI CVT

Automatic Transmission Fluid

DESCRIPTION AND APPLICATION

ATF CVT, designed with synthetic technology, ensures excellent lubrication and superior protection under all climate conditions. It is specially developed with high-quality base oils and advanced additive technology for continuously variable automatic transmissions (CVT), providing exceptional performance with extended oil change intervals. Suitable for use in passenger vehicles equipped with continuously variable automatic transmissions (CVT).

FEATURES AND BENEFITS

- Reduces wear under low temperatures and challenging operating conditions, extending the service life of the automatic transmission and lowering maintenance costs.
- Demonstrates excellent performance at both extremely low and high temperatures.
- Provides extended oil change intervals thanks to superior oxidation stability and wear resistance.
- Minimizes friction across a wide range of operating temperatures, reduces heat distribution, and ensures smooth and quiet transmission operation.

PERFORMANCE

Meets the performance specifications of: HYUNDAI/KIA CVT-1/SP-III, MINI COOPER EZL 799/799A/ZF CVT V1, MITSUBISHI CVT-F-J1/J4/J4+, NISSAN NS-1/NS-2/NS-3/N-CVT, OPEL/VAUXHALL CVT, PEUGEOT PSA 9735E, AUDI MULTITRONIC, BMW MINI COOPER EZL 799A, CHERY CVT/WCF-1, CITROEN PSA 9735E, DODGE/JEEP/CHRYSLER NS-2/CVT+4, FIAT TUTELA CVT, GM/SATURN DEX-CVT/1940713/CVTF, HONDA HMMF/HCF2/Z-1, RENAULT ELF MATIC CVT, SUBARU ICVT/FG/ECVT/NS2, SUZUKI CVTF TC/3320/4401/NS2, SUZUKI CVT FLUID GREEN 1 AND 2/1V, TOYOTA CVT FLUID TC/FE, VOLVO CVT 4959, VW/AUDI TL 521 16, VW/AUDI TL 521 80.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran transmission fluid should not come into contact with skin or eyes, should not be swallowed, and its vapors should not be inhaled. In case of contact with skin or eyes, rinse thoroughly with soap and water and seek medical attention if necessary. If swallowed, do not induce vomiting and seek emergency medical attention. If vapors are inhaled, take deep breaths and seek medical help if needed. Used Lubran fluids must not be discharged into drains, sewers, or the environment. They should be collected in designated waste oil containers and delivered to authorized recycling centers in accordance with applicable regulations. They must not be mixed with other petroleum derivatives or chemicals and should not be burned in stoves or furnaces. Empty containers should not be disposed of in landfills or the environment but handed over to licensed recycling organizations. For detailed information, you can review the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran fluid packages should not be exposed to direct sunlight for extended periods. Packages must not come into contact with water. Fluids should not come into contact with dust and should be kept away from dusty environments. The ambient temperature should not exceed 40°C. The proper use of this product in compliance with current laws and regulations is the sole responsibility of the user. Lubran cannot be held liable for any damages or adverse effects resulting from improper use, deviations from the intended purpose, or the product's inherent hazards.

TYPICAL PROPERTIES

| PHYSICAL PROPERTY | METHOD | CVT |
|------------------------------------|-------------|-------|
| Density, g/cm ³ at 15°C | ASTM D 4052 | 0,845 |
| Kinematic Viscosity, cSt, 100°C | ASTM D 445 | 6,1 |
| Viscosity Index | ASTM D 2270 | 150 |
| Pour Point, °C, max | ASTM D 97 | -38 |
| Flash Point, °C, min | ASTM D 92 | 210 |

PACKAGING TYPES

