

## MOTOJET 4T 20W-40



### 4-Stroke Motorcycle Oils

#### DESCRIPTION AND APPLICATION

Produced from high-quality mineral base oils and premium performance additives, this is a high-performance 4-stroke motorcycle oil. It can be used safely in 4-stroke motorcycles.

#### FEATURES AND BENEFITS

- Provides superior protection against wear with its high-quality additives, extending engine life.
- Delivers excellent performance in both air-cooled and water-cooled engines.
- Protects against rust and corrosion, extending the life of metal parts.
- Detergent properties prevent sludge and deposit formation, keeping the engine clean.
- Its high viscosity index and thermal stability ensure excellent engine protection at both high and low temperatures.
- Prevents efficiency losses caused by frequent starts and stops, ensuring high engine durability and fuel efficiency.
- Enhances the performance of catalytic converter-equipped engines.
- The specially formulated additive combination provides superior protection against wear, sludge, and deposits.

#### PERFORMANCE

Meets the performance requirements of API SL and JASO MA.

#### HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with eyes, be ingested, or inhaled. If contact occurs with the skin or eyes, wash thoroughly with soap and water, and seek medical assistance. In case of inhalation, move to fresh air and seek medical attention. If swallowed, do not induce vomiting and immediately seek medical help. Used Lubran motor oil should not be disposed of via regular trash, drainage systems, or unauthorized collection points. Waste oil must be delivered to designated collection facilities. Do not burn any petroleum product or mix it with chemicals. Keep out of reach of children. Empty containers should not be reused and must be disposed of properly. For detailed information, please refer to the "Material Safety Data Sheet."

#### STORAGE CONDITIONS

Lubran motor oils should not be exposed to direct sunlight for extended periods. Containers should be kept in clean and dust-free environments. Avoid storing the product at temperatures exceeding 40°C. It is recommended to use the product within the timeframe specified by the manufacturer. Lubran is not responsible for any damages resulting from improper storage conditions or negligence.

#### TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	4T 20W-40
Density, g/cm <sup>3</sup> at 15°C	ASTM D 4052	0,878
Kinematic Viscosity, cSt, 100°C	ASTM D 445	12,5-16,3
Viscosity Index, min	ASTM D 2270	120
Pour Point, °C, max	ASTM D 97	-21
Flash Point, °C, min	ASTM D 92	230

#### PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.  
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE